

BUMPER PAINT TEXTURISED GREY FZL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 - Product identifier

Trade name/designation BUMPER PAINT TEXTURISED GREY FZL

Chemical name

Product-type Mixture

Product code 3612-FZL

1.2 - Relevant identified uses of the substance or mixture and uses advised against

Uses advised against - Not suitable for home work (DIY).

1.3 - Details of the supplier of the safety data sheet

MIX PLAST SARL

ZA de l'avenir - Le devois

30600 Vestric et Candiac France

Telephone : +33 466 711 447 Fax +33 466 711 643

Website www.mix.fr

sds contact: +33(0)466 711 447 fds@mix.fr

1.4 - Emergency telephone number

SECTION 2: Hazards identification

2.1 - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Irritation, Category 2
Eye Irrit. 2	Eye irritation - Category 2
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)
STOT RE 2	STOT-repeated exposure - Category 2
Flam. Liq. 3	Flammable liquid and vapour. - Category 3
STOT SE 3 (H335)	STOT-single exposure - Category 3 (H335)
Aquatic Chronic 3	Hazardous to the aquatic environment - Aquatic Chronic 3

2.2 - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains: 2-methylpropan-1-ol, iso-butanol (CAS No.: 78-83-1)||Hydrocarbons, C9, aromatics (CAS No.:)||n-butyl acetate (CAS No.: 123-86-4)||Xylene (CAS No.: 1330-20-7)

Signal word : Warning

Hazard pictograms



Hazard statements

H226	Flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation



BUMPER PAINT TEXTURISED GREY FZL

H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs lung, kidneys, liver, skin through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Precautionary statements

P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P312	Call a a POISON CENTER, a doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
EUH-phrases	: None

2.3 - Other hazards

SECTION 3: Composition / information on ingredients

3.1 - Substances

Not applicable

3.2 - Mixtures

Chemical name	No	%	Class	Spec. concentrations
n-butyl acetate	CAS No. : 123-86-4 Index No. : 607-025-00-1 EC No. : 204-658-1	20 - 30	Flam. Liq. 3 - H226 STOT SE 3 (H336) - H336	Not applicable
Xylene	CAS No. : 1330-20-7 Index No. : 601-022-00-9 EC No. : 215-535-7	10 - 20	Acute Tox. 4 Dermal - H312 Acute Tox. 4 Inhalation - H332 Asp. Tox. 1 - H304 Eye Irrit. 2 - H319 Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 STOT RE 2 - H373 STOT SE 3 (H335) - H335	Not applicable
2-methoxy-1-methylethyl acetate	CAS No. : 108-65-6 Index No. : 607-195-00-7 EC No. : 203-603-9	0 - 6	Flam. Liq. 3 - H226 STOT SE 3 (H336) - H336	Not applicable
1-methoxy-2-propanol, monopropylene glycol methyl ether	CAS No. : 107-98-2 Index No. : 603-064-00-3 EC No. : 203-539-1	0 - 6	Flam. Liq. 3 - H226 STOT SE 3 (H336) - H336	Not applicable
2-methylpropan-1-ol, iso-butanol	CAS No. : 78-83-1 Index No. : 603-108-00-1 EC No. : 201-148-0	1 - 3	Eye Dam. 1 - H318 Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 STOT SE 3 (H335) - H335 STOT SE 3 (H336) - H336	Not applicable
Hydrocarbons, C9, aromatics	CAS No. : Index No. : EC No. : 918-668-5	0 - 3	Aquatic Chronic 2 - H411 Asp. Tox. 1 - H304 Flam. Liq. 3 - H226 STOT SE 3 (H335) - H335 STOT SE 3 (H336) - H336	Not applicable
Ethylbenzene	CAS No. : 100-41-4 Index No. : 601-023-00-4 EC No. : 202-849-4	0,14 - 0,15	Acute Tox. 4 Inhalation - H332 Aquatic Chronic 3 - H412 Asp. Tox. 1 - H304 Flam. Liq. 2 - H225 STOT RE 2 - H373	Not applicable

SECTION 4: First aid measures

BUMPER PAINT TEXTURISED GREY FZL

4.1 - Description of first aid measures

Following inhalation

- Call a physician immediately.
- Remove casualty to fresh air and keep warm and at rest.
- If breathing is irregular or stopped, administer artificial respiration.

Following skin contact

- Remove contaminated, saturated clothing immediately.
- After contact with skin, wash immediately with plenty of water and soap.
- In case of skin irritation, consult a physician.

After eye contact

- Remove contact lenses, if present and easy to do. Continue rinsing.
- Rinse immediately carefully and thoroughly with eye-bath or water.
- Call a physician immediately.

After ingestion

- Let water be drunken in little sips (dilution effect).
- Rinse mouth thoroughly with water.
- Do NOT induce vomiting.
- Call a physician immediately.

4.2 - Most important symptoms and effects, both acute and delayed

Symptoms and effects - Following inhalation

- No information available.

Symptoms and effects - Following skin contact

- Causes skin irritation.

Symptoms and effects - After eye contact

- No information available.

Symptoms and effects - After ingestion

- No information available.

4.3 - Indication of any immediate medical attention and special treatment needed

- No information available.

SECTION 5: Firefighting measures

5.1 - Extinguishing media

Suitable extinguishing media

- Foam
- Extinguishing powder
- carbon dioxide

Unsuitable extinguishing media

- Full water jet

5.2 - Special hazards arising from the substance or mixture

Special hazards arising from the substance or mixture

- Explosion risk in case of fire.
- In case of fire and/or explosion do not breathe fumes.

5.3 - Advice for firefighters

- Co-ordinate fire-fighting measures to the fire surroundings.
- Do not allow run-off from fire-fighting to enter drains or water courses.
- Ensure all waste water is collected and treated via a waste water treatment plant.

BUMPER PAINT TEXTURISED GREY FZL

- Use water spray jet to protect personnel and to cool endangered containers.
- Special protective equipment for firefighters
- firefighter boots (HO A29 or A30)
- flame arrestor combination (EN469)
- Container device with compressed air (DIN EN 137)
- flameproof gloves (EN 659)

SECTION 6: Accidental release measures

6.1 - Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

- Use personal protection equipment.
- Remove persons to safety.
- Keep away from sources of ignition - No smoking.
- Keep away from heat.
- Safe handling: see section 7
- Wear personal protection equipment (refer to section 8).

For emergency responders

- Wear personal protection equipment (refer to section 8).
- Evacuate area.
- Remove all sources of ignition.
- Keep away from heat.
- Safe handling: see section 7

6.2 - Environmental precautions

- Do not allow to enter into soil/subsoil.
- Do not allow to enter into surface water or drains.

6.3 - Methods and material for containment and cleaning up

Methods and material for containment

- Take up mechanically, placing in appropriate containers for disposal.
- SECTION 10: Stability and reactivity

Methods and material for cleaning up

- Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
- Wash with plenty of water.
- Ventilate affected area.

Inappropriate techniques

- Keep away from .? (incompatible materials to be indicated by the manufacturer).

6.4 - Reference to other sections

- Disposal: see section 13
- Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1 - Precautions for safe handling

Recommendation

- Avoid: Skin contact
- It is recommended to design all work processes always so that the following is excluded: Skin contact

BUMPER PAINT TEXTURISED GREY FZL

- Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
- Vapours are heavier than air, spread along floors and form explosive mixtures with air.
- Take precautionary measures against static discharges.
- Discharge into the environment must be avoided.
- Contaminated work clothing should not be allowed out of the workplace.
- Do not eat, drink or smoke when using this product.

Advices on general occupational hygiene

- No information available.

7.2 - Conditions for safe storage, including any incompatibilities

- Keep away from heat.
- Keep container tightly closed in a cool, well-ventilated place.
- Keep/Store only in original container.
- Remove all sources of ignition.
- When using do not smoke.
- Keep away from clothing as well as other incompatible materials.
- SECTION 10: Stability and reactivity

7.3 - Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 - Control parameters

8.2 - Exposure controls

Appropriate engineering controls

- No information available.

Individual protection measures, such as personal protective equipment

- When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.



- DIN EN 374

- Suitable protective clothing: Full protection suit



- Required properties: antistatic
- Directive 89/686/CEE & EN ISO 20344
- Gently wash with plenty of soap and water.
- Suitable eye protection: Eye glasses with side protection



- DIN EN 166

BUMPER PAINT TEXTURISED GREY FZL

- Suitable respiratory protection
apparatus: Respiratory protection
helmet/hood



- Combination filtering device (EN
14387)

- Suitable protective clothing: Chemical
resistant safety shoes



SECTION 9: Physical and chemical properties

9.1 - Information on basic physical and chemical properties

Physical state	Liquid	Appearance	Liquid
Colour	grey	Odour	Typical solvent
Odour threshold		No data available	
pH		No data available	
Melting point		No data available	
Freezing point		No data available	
Boiling point		No data available	
Flash point		23 °C < V < 60 °C	
Evaporation rate		No data available	
flammability		> 23 °C	
Lower explosion limit		1,2 % Vol. 15°C	
Upper explosion limit		7,6 % Vol. 15°C	
Vapour pressure		No data available	
Vapour density		No data available	
Relative density		1,212 20°C	
Density		No data available	
Solubility (Water)		not soluble	
Solubility (Ethanol)		No data available	
Solubility (Acetone)		No data available	
Solubility (Organic solvents)		No data available	
Log KOC		No data available	
Auto-ignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

9.2 - Other information

VOC content	30,44 % 369.54 g/l
Minimum ignition energy	No data available



BUMPER PAINT TEXTURISED GREY FZL

Conductivity	No data available
--------------	-------------------

- VOC (Directive 2004/42 / EC):
Special Finishes.
VOC expressed in g / liter of product ready for use:
Maximum limit: 840
Product VOC: 608.54
- Diluted with: 20.00% (P / P) DILUANT 3616A

SECTION 10: Stability and reactivity

10.1 - Reactivity

- This material is considered to be non-reactive under normal use conditions.
- 2-METHOSSIS-1-METHYLETYLACETATE: stable, but with air can slowly give peroxides that explode due to the increase in temperature.
- 1-METHOSSIS-2-PROPANOL: absorbs and dissolves in water and organic solvents, dissolves different plastics; it's stable but with air can slowly give explosives to peroxides.

10.2 - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 - Possibility of hazardous reactions

- In use may form flammable/explosive vapour-air mixture.
- N-BUTYL ACETATE: Vapors may form explosive mixtures with air.
- ISOBUTANOL: reacts violently with organic acids. Explosive reaction with halogens, phosphorus trichloride.
- 2-METHOXY-1-METHYLETHYL ACETATE: It may react violently with oxidants and strong acids and alkali metals.
- 1-METHOSSIS-2-PROPANOL: may react dangerously with strong oxidizing agents and strong acids.
- ETHYLBENZENE: Reacts violently with strong oxidants and corrodes various types of plastic materials. May form explosive mixtures on contact with air.

10.4 - Conditions to avoid

- Take precautionary measures against static discharges.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container dry.
- Do not allow contact with air.
- N-BUTYLACETAT : Heat, sparks and open flames. Avoid the accumulation of electrostatic charges.
- ETHYLBENZENE: heating.
- ISOBUTANOL: avoid $T^{\circ}C > 30$. keep the product away from open flames.
- 2-METHOXY-1-METHYLETHYL ACETATE: Store in an inert, moisture-proof manner because it is easily hydrolyzed.
- 1-METHOXY-2-PROPANOL: avoid exposure to air.

10.5 - Incompatible materials

- Acid
- Water
- nitrates
- Highly oxidising substances
- potassium t-butoxide
- Nitric acid

BUMPER PAINT TEXTURISED GREY FZL

- Sulphuric acid and sulphurous acid
- Oxidising agent
- Alkali metals

10.6 - Hazardous decomposition products

- Thermal decomposition can lead to the escape of irritating gases and vapours.
- ISOBUTANOL: CO, CO₂.
- N-BUTYL ACETATE : Thermal decomposition or fire can release potentially dangerous gases and vapors.
- ETHYLBENZENE: methane, styrene, hydrogen, ethane.

SECTION 11: Toxicological information

11.1 - Information on toxicological effects

Acute toxicity - Not classified

Toxicity : Mixture

LD50 oral (rat)	No data available
LD50 dermal (rat)	No data available
LD50 dermal (rabbit)	No data available
LC50 inhalation (rat)	No data available
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

- Based on available data, the classification criteria are not met.

Toxicity : Substances

n-butyl acetate (123-86-4)	
LD50 oral (rat)	> 12000 mg/kg
LD50 dermal (rabbit)	> 14000 mg/kg
LC50 inhalation (rat)	0.74 mg/l/4h
Xylene (1330-20-7)	
LD50 oral (rat)	> 3500 mg/kg
LD50 dermal (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 4200 mg/kg
LC50 inhalation (rat)	6.700 ppm (4h)
2-methoxy-1-methylethyl acetate (108-65-6)	
LD50 oral (rat)	6190 mg/kg
LD50 dermal (rat)	> 2000 mg/kg
Ethylbenzene (100-41-4)	
LD50 oral (rat)	3500 mg/kg
LD50 dermal (rabbit)	15400 mg/kg

Skin corrosion/irritation - Irritation, Category 2 - Causes skin irritation
- Irritating to skin.

Serious eye damage/eye irritation - Eye irritation - Category 2 - Causes serious eye irritation

BUMPER PAINT TEXTURISED GREY FZL

<u>Respiratory or skin sensitisation</u>	- Not classified
<u>Germ cell mutagenicity</u>	- Not classified
<u>Carcinogenicity</u>	- Not classified
<u>Reproductive toxicity</u>	- Not classified
<u>STOT-single exposure</u>	- STOT-single exposure - Category 3 (H336) - May cause drowsiness or dizziness - STOT-single exposure - Category 3 (H335) - May cause respiratory irritation
<u>STOT-repeated exposure</u>	- STOT-repeated exposure - Category 2 - May cause damage to organs lung, kidneys, liver, skin through prolonged or repeated exposure
<u>Aspiration hazard</u>	- Not classified

SECTION 12: Ecological information

12.1 - Toxicity

Toxicity : Mixture

EC50 48 hr crustacea	No data available
LC50 96 hr fish	No data available
ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

Toxicity : Substances

n-butyl acetate (123-86-4)	
EC50 48 hr crustacea	44 mg/l
LC50 96 hr fish	18 mg/l
ErC50 algae	397 mg/l 72h
ErC50 other aquatic plants	397 mg/l 72h
NOEC chronic crustacea	23,2 mg/l
NOEC chronic algae	196 mg/l
NOEC chronic other aquatic plants	196 mg/l
Xylene (1330-20-7)	
LC50 96 hr fish	2,6 mg/l
ErC50 algae	1,9 mg/l
ErC50 other aquatic plants	1,9 mg/l
NOEC chronic fish	> 1,3 mg/l
NOEC chronic crustacea	1,17 mg/l
2-methoxy-1-methylethyl acetate (108-65-6)	
EC50 48 hr crustacea	> 500 mg/l
LC50 96 hr fish	> 100 mg/l

BUMPER PAINT TEXTURISED GREY FZL

ErC50 algae	> 1000 mg/l 72h
ErC50 other aquatic plants	> 1000 mg/l 72h
NOEC chronic fish	47,5 mg/l
NOEC chronic crustacea	> 100 mg/l
NOEC chronic algae	>= 1000 mg/l
NOEC chronic other aquatic plants	>= 1000 mg/l
Ethylbenzene (100-41-4)	
EC50 48 hr crustacea	> 5,2 mg/l
LC50 96 hr fish	5,1 mg/l
ErC50 algae	5,4 mg/l
ErC50 other aquatic plants	5,4 mg/l
NOEC chronic fish	3,3 mg/l
NOEC chronic crustacea	0,93 mg/l
NOEC chronic algae	3,4 mg/l
NOEC chronic other aquatic plants	3,4 mg/l

- The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

12.2 - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available
Chemical oxygen demand (COD)	No data available
% of biodegradation in 28 days	No data available

- No information available.

12.3 - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log KOC	No data available

- No indication of bioaccumulation potential.

12.4 - Mobility in soil

- No information available.

12.5 - Results of PBT and vPvB assessment

12.6 - Other adverse effects

- No information available.

SECTION 13: Disposal considerations

13.1 - Waste treatment methods

<u>Waste treatment methods</u>	<ul style="list-style-type: none"> - Dispose of waste according to applicable legislation. - Do not pierce or burn, even after use.
<u>Sewage disposal</u>	<ul style="list-style-type: none"> - Do not allow to enter into surface water or drains. - Do not allow run-off from fire-fighting to enter drains or water courses.



BUMPER PAINT TEXTURISED GREY FZL

<u>Special precautions for waste treatment</u>	- Send to a hazardous waste incinerator facility under observation of official regulations. - Land transport (ADR/RID)
--	---

<u>Community or national or regional provisions</u>	- Observe in addition any national regulations!
---	---

SECTION 14: Transport information

14.1 - UN number

<u>UN number (ADR)</u>	:	UN1263
<u>UN number (RID)</u>	:	UN1263
<u>UN number (IMDG)</u>	:	UN1263
<u>UN number (IATA)</u>	:	UN1263

14.2 - UN proper shipping name

<u>UN proper shipping name (ADR)</u>	:	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) 640E
<u>UN proper shipping name (RID)</u>	:	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) 640E
<u>UN proper shipping name (IMDG)</u>	:	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) 640E
<u>UN proper shipping name (IATA)</u>	:	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) 640E

14.3 - Transport hazard class(es)

BUMPER PAINT TEXTURISED GREY FZL

ADR Transport hazard class(es) : 3

ADR Classification code: : F1

Pictograms



Transport hazard class(es) (RID) : 3

Pictograms



Transport hazard class(es) (IMDG) : 3

Pictograms



Transport hazard class(es) (IATA) : 3

Pictograms



14.4 - Packing group

Packing group : III

Packing group (RID) : III

Packing group (IMDG) : III

Packing group (IATA) : III

14.5 - Environmental hazards

Environmental hazards : No

Marine pollutant : No

14.6 - Special precautions for user



BUMPER PAINT TEXTURISED GREY FZL

ADR

<u>ADR Classification code:</u>	:	F1
<u>ADR Special provisions</u>	:	163+ 640E+650+367
<u>ADR Limited quantity (LQ)</u>	:	5 L
<u>ADR Excepted quantities</u>	:	E1
<u>ADR Packing instructions</u>	:	P001 IBC03 LP01 R001
<u>ADR Special packing provisions</u>	:	PP1
<u>ADR Mixed packing provisions</u>	:	MP19
<u>Instructions for portable tanks and bulk containers</u>	:	T2
<u>Special provisions for portable tanks and bulk containers</u>	:	TP1 TP29
<u>ADR tank code</u>	:	LGBF
<u>ADR tanks special provisions</u>	:	
<u>Vehicle for tank carriage</u>	:	FL
<u>ADR Transport category</u>	:	3
<u>ADR Tunnel restriction code</u>	:	D/E
<u>ADR Special provisions loading, unloading and handling</u>	:	
<u>Special provisions - Packages</u>	:	V12
<u>Special provisions - Bulk</u>	:	
<u>Special provisions - Operation</u>	:	S2
<u>ADR Hazard identification number (Kemler No.)</u>	:	30

RID

<u>Special provisions</u>	:	640E
<u>Limited quantity (LQ)</u>	:	5 L
<u>Excepted quantities</u>	:	

IMDG

<u>Special provisions</u>	:	
<u>Limited quantity (LQ)</u>	:	5 L
<u>Excepted quantities</u>	:	
<u>Packing instructions</u>	:	
<u>Special packing provisions</u>	:	
<u>IBC instruction(s)</u>	:	
<u>IBC provisions</u>	:	
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>EmS codes</u>	:	F-E, S-E
<u>Stowage and handling</u>	:	
<u>Segregation</u>	:	
<u>Properties and observations</u>	:	



BUMPER PAINT TEXTURISED GREY FZL

IATA

PCA - Excepted quantities	:	
PCA - Limited Quantity - Packing Instructions	:	
PCA - Limited Quantity - Maximum Net Quantity per Package	:	
PCA - Packing Instructions	:	355
PCA - Maximum Net Quantity per Package	:	60 L
CAO - Packing Instructions	:	366
CAO - Maximum Net Quantity per Package	:	220 L
Special Provisions	:	A3, A72, A192
ERG Code	:	

14.7 - Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1 - Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances REACH candidates	None
Substances Annex XIV	None
Substances Annex XVII	None

VOC content 30,44 %

15.2 - Chemical Safety Assessment

Chemical safety assessment carried out for the product - No information available.

SECTION 16: Other information

SDS versions

Version	Issue date	Description of the amendments
5	02/12/2019	SECTION 3.2 / SECTION 5.1 / SECTION 8.2 / SECTION 9.2 / SECTION 10 / HEADING 15.1
4	23/07/2019	SECTION 9.2: VOC change SECTION 15: VOC change
3	27/03/2019	SECTION 2: Addition: H335 - H412 - P273 - P403 + 233 - Hydrocarbons, C9, aromatics - 2-methylpropan-1-ol, isobutanol Less: P210 - P280 - P304 + P378 - EUH066 SECTION 3: Added: H336 to 2-methoxy-1-methylethyl acetate. SECTION 9: Addition: Color - VOC information after dilution

BUMPER PAINT TEXTURISED GREY FZL

Version	Issue date	Description of the amendments
2	18/10/2018	SECTION 1: Identification of the substance / mixture and company / undertaking SECTION 2: Hazard identification SECTION 3: Composition / information on ingredients SECTION 4: First aid SECTION 6: Accidental release measures SECTION 7: Handling and storage SECTION 8: Exposure controls / personal protection SECTION 9: Physical and chemical properties SECTION 11: Toxicological information SECTION 12: Ecological Information SECTION 13: Disposal considerations SECTION 14: Transport information SECTION 15: Regulatory information SECTION 16: Other information
1	15/01/2015	

Texts of the regulatory sentences

Acute Tox. 4 Dermal	Acute toxicity (dermal) - Category 4
Acute Tox. 4 Inhalation	Acute toxicity (inhalative) - Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment - Aquatic Chronic 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Aquatic Chronic 3
Asp. Tox. 1	Aspiration hazard - Category 1
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation - Category 2
Flam. Liq. 2	Flammable liquid and vapour. - Category 2
Flam. Liq. 3	Flammable liquid and vapour. - Category 3
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs lung, kidneys, liver, skin through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects
Skin Irrit. 2	Irritation, Category 2
STOT RE 2	STOT-repeated exposure - Category 2
STOT SE 3 (H335)	STOT-single exposure - Category 3 (H335)
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)



BUMPER PAINT TEXTURISED GREY FZL

*** **